

Direct Fab® is treated for direct dye sublimation printing by dipping. Unlike traditional dye sublimation printing, you can print an image onto the fabric directly without transfer paper. DSatin has glossy surface type and provides highly ink absorption, strong durability and anti-shrinkage effect to prevent the material shrinkage on heating process. With the softness and strong durability, it is suitable for all kinds of indoor or outdoor signages. In comparison with traditional dye sublimation printing, you will be able to save much more cost and working time as well as avoid the various problems, such as skewing, wrinkling and so on.

Application

■ Synthetic Canvas	■ Roll up Banner	■ Instant banner	■ Wall advertising
■ Outdoor, Indoor signs	■ Booth Display	■ Textile (Roll up) Blinds	■ POP-up exhibits

Recommended Printers

D.gen	Mimaki	ATPColor	Mutoh
★★★★★	★★★★★	★★★★★	★★★★★

Technical data

Base material	100% polyester SATIN	Compatible Ink	Dye Sublimation Ink
Denier	75 X 300	Ink limit	250%
Total weight(g/m²)	170 ± 2	Surface finish	satin
Thickness(μm)	253 ± 2	Optimum printer temp.	70°F(21°C)
Threads per Inch	66T	Relative humidity (RH)	20~60%
Tensile strength (Kg/mm²)		Life expectancy	Indoor : 6 months
Color(CIE Mesearment)			Outdoor : 3 months

Roll Specification

Width	Gross Weight / roll (Kg/roll)	Roll length	50m
60" (1520mm)	14.8	Diameter of Core	2 inch
		Thickness of Core	4 mm

Performance features

<ol style="list-style-type: none"> 1) Compatible with all kinds of dye sublimation printers and ink 2) True color reproduction with rapid drying times 3) Save transfer paper cost by printing directly to fabric 4) No ink is lost in the transfer process, prints come out in brighter, more saturated colors. 5) Wrinkle-free performance, even after long-term storage.
--

Remark

<ol style="list-style-type: none"> 1) MOQ (Minimum Order Quantity): 72 rolls / 2 pallets 2) 1 pallets = 6 rolls X 6 rolls (36 rolls) 3) Offer: FOB Pusan, South Korea 4) Estimated Delivery time: 7 days by Air / 5~6 weeks by ship 5) When the defect on quality come up, we will replace that material by the new roll.
--



Should you have any inquiries, feel free to contact us.
 Tel) +44 (0)208 546 1717, Fax) +44 (0)208 546 1717
 Email: sales@sslinkltd.co.uk, Web site: <http://www.sslinkltd.co.uk>