

Thin woven polyester fabric combined with a water resistant matte surface to produce exceptional printed resolution and high definition. Light, soft and durable photo fabric that have no curl under the tension. With lightness and softness of the material, it can be installed and displayed quickly and conveniently. Universally compatible with Eco-solvent, Mild-solvent and True-solvent ink.

Application

■ POS	■ Banner Stand	■ Hanging Banner	■ Tensioned Banner
■ Exhibition Graphics	■ Short term Event Flag	■ Roll up Blinds	■ Indoor, outdoor signs

Compatible Printers

Mimaki(JV3,JV5)	Vutek(UltraVu®)	Roland(SJ,AJ)	Mutoh(Rockhopper, spitfire)
★★★★★	★★★★★	★★★★★	★★★★★

Technical data

Base material	100% polyester Woven fabric	Compatible Ink	Solvent/Eco/Mild solvent ink
Denier	150 x 150	Ink limit	200%
Total weight(g/m ²)	130	Surface finish	Matt
Tolerance	±2	Optimum printer temp.	70°F (21 °C)
Thickness(μm)	180	Relative humidity (RH)	20~60%
Tolerance	±2	PVC Free	O
Threads per Inch	60 T	Fire Retardant	X
Color(CIE Mesearment)	L*:97 a*:1.2 b*:-6.5	Water resistant	O
Tensile strength (Kg/mm ²)	MD: 60, TD: 42		

Roll Specification

Width	Gross Weight / roll (Kg/roll)	Roll length	50 yds (45.7meter)
36" (914mm)	6.99	Diameter of Core	3 inch
42" (1050mm)	7.98	Thickness of Core	4 mm
50" (1270mm)	9.49		
54" (1370mm)	10.26		
60" (1520mm)	11.29		

Performance features

<ol style="list-style-type: none"> 1) Compatible with Solvent, Eco-solvent and Mild solvent 2) True color reproduction with rapid drying times 3) No edge-curl when under tension 4) Moisture resistant for short-term outdoor applications 5) Wrinkle-free performance, even after long-term storage. 6) Durable, universal coating eliminates cracking of the ink layer due to stretching in tensioned or weighted applications.
--



Should you have any inquiries, feel free to contact us.

Tel) +44 (0)208 546 1717, Fax) +44 (0)208 546 1717

Email: sales@sslinkltd.co.uk, Web site: <http://www.sslinkltd.co.uk>