

Thin woven polyester fabric combined with a water resistant matte surface to produce exceptional printed resolution and high definition. Light, soft and durable photo fabric that have no curl under the tension. Universally compatible with dye / pigmented waterbased ink. With lightness and softness of the material, it can be installed and displayed easily and freely.

Application

■ Outdoor/Indoor signs	■ Banner Stand	■ Hanging banner display	■ Tensioned banner display
■ Flying banner	■ Short term Event Flag	■ Roll up Blinds	■ POP-up exhibits

Compatible Printers

HP Designjet	Epson	Roland/Mimaki	Novajet
★★★★★	★★★★★	★★★★★	★★★★★

Technical data

Base material	100% polyester Woven fabric	Compatible Ink	Dye/Pigment
Denier	150 x 150	Ink limit	200%
Total weight(g/㎡)	110	Surface finish	Matt
Tolerance	±2	Optimum printer temp.	70°F (21 °C)
Thickness(μm)	160	Relative humidity (RH)	20~60%
Tolerance	±2	PVC Free	O
Threads per Inch	60 T	Fire Retardant	X
Color(CIE Meseartment)	L*: 96 a*: 1.3 b*: -5.5	Water resistant	O
Tensile strength (Kg/㎡)	MD: 54 , TD:35		

Roll Specification

Width	Gross Weight / roll (Kg/roll)	Roll length	66 yds (60meter)
36" (914mm)	7.2	Diameter of Core	2 inch
42" (1050mm)	8.3	Thickness of Core	4 mm
50" (1270mm)	9.8		
54" (1370mm)	10.5		
60" (1520mm)	11.7		

Performance features

<ol style="list-style-type: none"> 1) Compatible with dye and pigment inks. 2) True color reproduction with rapid drying times 3) No edge-curl when under tension 4) Moisture resistant for short-term outdoor applications 5) Wrinkle-free performance, even after long-term storage. 6) Durable, universal coating eliminates cracking of the ink layer due to stretching in tensioned or weighted applications.
--



Should you have any inquiries, feel free to contact us.
 Tel) +44 (0)208 546 1717, Fax) +44 (0)208 546 1717
 Email: sales@sslinkltd.co.uk, Web site: <http://www.sslinkltd.co.uk>