

Product Data Sheet**WBL****PET Backlit film, front print- Matte, 270 g****For Dye/pigment ink**

A translucent, front-print Backlit film. Matt type and printable directly on the surface. It delivers an excellent colour and high intensity of illumination effect with Dye/Pigment Ink. Specially, brilliant advertising effect with illuminated signs. It is widely used at trade shows and exhibitions and very suitable for any type of signs with illumination indoor and outdoor use.

Application

■ Outdoor/Indoor signs	■ Illuminated showcases	■ Display exhibitions	■ Wide color display with light
■ City billboards	■ Subway billboards	■ Available any kinds of illuminated display	

Compatible Printers

HP Designjet	Epson	Roland/Mimaki	Novajet
★★★★★	★★★★★	★★★★★	★★★★★

Technical data

Base material	PET	Compatible Ink	Dye/Pigment
Total weight(g/㎡)	270	Ink limit	200%
Tolerance	±3	Surface finish	Matt
Total thickness(μm)	213	Optimum printer temp.	70°F (21 °C)
Tolerance	±3	Relative humidity (RH)	20~50%
Released Film(Paper)	x	Water resistant	O
Adhesive	x	Adhesive	X
Tensile strength (Kg/㎡)	MD:53 , TD: 90		
Heat shrink rate (%)	MD: 0.1, TD: 0.1		

Roll Specification

Width	Gross Weight / roll (Kg/roll)	Roll length	30meter
36"(914mm)	8.5	Diameter of Core	3 inch
50" (1270mm)	11.7	Thickness of Core	4 mm
60" (1520mm)	14.1		

Remark

1) MOQ (Minimum Order Quantity): 98 rolls / 2 pallets
2) 1 pallets = 7 rolls X 7 rolls (49 rolls)
3) Offer: FOB Pusan, South Korea
4) Estimated Delivery time: 7 days by Air 5~6 weeks by ship
5) When the defect on quality come up, we will replace that material by the new roll.



Feel free to contact us via contact points below if you have any questions
 Tel) +44 (0)208 546 1717, Fax) +44 (0)208 546 1717
 Email: sales@sslinkltd.co.uk, Web site: <http://www.sslinkltd.co.uk>