

Gray and white self-adhesive PP synthetic paper which is perfectly absorb water based ink, e.g. dye and pigment ink. Colour effect is excellent with Backlighting by light dispersion / Water-resistant. It makes possible to print on a variety of wide format plotters. 3C-SPG delivers accurate colours and vivid results on its high-quality Matt surface. It's excellent for indoor signage.

Application

| | | | |
|-----------------------------|-------------------------------|---------------------------------------|------------------|
| ■ Non-Light dispersion sign | ■ Photo stickers | ■ Graphic arts | ■ Photo stickers |
| ■ Backlit display | ■ Light dispersion signboards | ■ Pictures for the digital camera etc | |

Recommended Printers

| | | | |
|--------------|-------|---------------|---------|
| HP Designjet | Epson | Roland/Mimaki | Novajet |
| ★★★★★ | ★★★★★ | ★★★★★ | ★★★★★ |

Compatible Printers

| | | | |
|---|-------------------------------|-------------------------------|------------------|
| Base material | PP Synthetic Paper 80 μ m | Compatible Ink | Dye/Pigment |
| Total weight(g/ m²) | 190 | Ink limit | 200% |
| Tolerance | ±3 | Surface finish | Matte |
| Total thickness(μm) | 193 | Optimum printer temp. | 70°F (21 °C) |
| Tolerance | ±3 | Relative humidity (RH) | 20~50% |
| Released film weight(g/ m²) | 74 | Life expectancy | Indoor: 1year |
| Adhesive | Gray Adhesive | | Outdoor: 3months |
| Released film thickness(μm) | PET 50 μ m | Water resistant | O |
| | | | |

Roll Specification

| | | | |
|--------------|--------------------------------------|--------------------------|---------|
| Width | Gross Weight / roll (Kg/roll) | Roll length | 30meter |
| 36"(914mm) | 6.3 | Diameter of Core | 2 inch |
| 42"(1067mm) | 7.2 | Thickness of Core | 4 mm |
| 50" (1270mm) | 8.6 | | |
| 60" (1520mm) | 10.4 | | |

Remark

| |
|---|
| 1) MOQ (Minimum Order Quantity): 98 rolls / 2 pallets |
| 2) 1 pallets = 7 rolls X 7 rolls (49 rolls) |
| 3) Offer: FOB Pusan, South Korea |
| 4) Estimated Delivery time: 7 days by Air 5~6 weeks by ship |
| 5) When the defect on quality come up, we will replace that material by the new roll. |



Feel free to contact us via contact points below if you have any questions
 Tel) +44 (0)208 546 1717, Fax) +44 (0)208 546 1717
 Email: sales@sslinkltd.co.uk, Web site: http://www.sslinkltd.co.uk